



## PRODUCT DATA SHEET

### PRODUCT: BIOSTRIP

#### Eco Friendly Release Agent

#### Description

Biostrip is a Biodiesel based releasing agent, for the construction industry  
Principal uses Biostrip is suitable for use on timber, steel and fibreglass shuttering

#### Advantages

- Biostrip is eco friendly and biodegradable
- A simple one coat application is required
- Cleaning is minimised
- Biostrip does not evaporate in the sun
- Build up on the shutter is eliminated

#### Performance data

Appearance:	Light/Medium Coloured Oil
Temperature Stability:	40°C
Flash Point:	198 °C
Odour:	Slight
Viscosity:	46
Physical Form:	Liquid
Shelf Life:	6 Months

#### Application

Apply as thinly as possible to entire surface of shutter by means of a paint brush, paint roller or low pressure spray

#### Coverage

Coverage is approximately 14-20m<sup>2</sup> per litre

#### Packaging

Biostrip is available in 210L and 25L drums

#### Safety & handling

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

#### Shelf Life & Storage

6 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

#### Note

Roll the drum or shake 25L before use to prevent settling out of the product

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAK Construction Chemicals quality control. We cannot be held responsible or liable, directly or in directly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.