

PRODUCT DATA SHEET

PRODUCT: AS7

Wax Shutter Release Agent

Description

AS7 is a wax based releasing and preserving agent.

Principal uses

AS7 is used to protect all timber shutter boards and as a release agent on steel and timber shuttering. **AS7** applied to form work and machinery will prevent rust and keep it free from concrete deposits

When **AS7** is used on steel shuttering it may leave yellowish brown stains on the concrete and is therefore not suitable for off-shutter concrete. If a plaster or paint finish is required after stripping it is advisable to degrease the surface first before applying a finish. Use **A.Shak Superstrip** for steel shutters when an off-shutter finish is required.

Performance data

Appearance:	Dark Brown liquid
Flash Point:	55 - 107deg C
Odour:	Slight
Physical Form:	Liquid
Viscosity at 100 C:	8 cst

Packaging

AS7 is available in 210L and 25L drums

Surface preparation

If the shutter board has been used previously make sure the surface is clean and free of cement deposits before oiling.

Safety & handling

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice.

Application

Apply as thinly as possible to shuttering by paint roller, brush or other suitable means. On timber and steel shutters, repeat application after shutters have been used once. Thereafter the shuttering can be used 3 - 4 times without further application of **AS7**.

Shelf life & storage instructions

6 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life.

Apply to untreated shutter board liberally to preserve the timber and extend the life of the board.

Note

Roll the drum or shake 25L before use to prevent settling out of the product.

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAK Construction Chemicals quality control. We cannot be held responsible or liable, directly or indirectly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.