



# PRODUCT DATA SHEET

## PRODUCT: 3B Grease Release Agent

### Description

3B GREASE is a paraffin wax based product

### Principal uses

- 3B GREASE is manufactured specifically for use on fibreglass coffer moulds
- It can also be used as a heavy-duty release agent on steel pre-cast moulds, steel shuttering and veneer shutter boards

### Performance data

Appearance:	Yellowish thick grease
Flash Point:	170°C
Odour:	Slight
Physical Form:	Thick wax
Congeaing:	74°C

### Application

Apply a thin layer of 3B Grease with a clean soft cloth. Ensure that the entire surface of the mould or shutter is covered with 3B Grease. Coverage is approximately 14 square metres per litre

### Coverage

Coverage is approximately 14m<sup>2</sup> per litre

### Packaging

3B Grease is available in 210L and 20L drums

### Safety & handling

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

### Shelf Life & Storage

6 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

### Note

Roll the drum before use to prevent settling out of the product

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAK Construction Chemicals quality control. We cannot be held responsible or liable, directly or in directly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.

